




38MT+™

HEAVY DUTY GEAR REDUCTION STARTER



CRANKS UP TO
4% FASTER
THAN THE COMPETITION

FEATURES & BENEFITS


- **Available* with Integrated Over Crank Protection (IOCP)**, a built-in circuit breaker, protects the starter from thermal damage, automatically resetting at a safe operating temperature while eliminating the need for a wiring harness.
- **38MT+ features an Integral Magnetic Switch (IMS)**. IMS reduces voltage drop and ensures the solenoid receives the maximum available voltage in any starting condition.
- **Electrical soft-start** consistently and accurately engages the pinion with the ring gear providing increased reliability.
- **Warranty:** Non-OCP model: 1 year / unlimited miles Integrated OCP model: 3 years / unlimited miles (Applicable to U.S. and Canada only)

* Part Number 8201084




Integrated Over-Crank Protection (IOCP)

COMPETITIVE COMPARISON



STARTER MODEL	OCP	FASTER CRANKING	WEIGHT
Delco Remy 38MT+	Optional	82 Engine RPM	28.44 lbs/12.9kg
Melco	No	79 Engine RPM	29.32lbs/13.3kg

38MT+™ HEAVY DUTY GEAR REDUCTION STARTER



SPECIFICATIONS

Engine Size	up to 13 liter
Rotation	Clockwise
Mounting	SAE #3
Pinion Data	12 Tooth, Mod 3-metric
Output	4.3kW peak at 12V
Weight	12.9 kg/28.44 lbs
Diameter	100 mm/3.94 inches
Heavy Duty Drive	Electrical Soft-Start, Engagement System, Overrunning Clutch

38MT+ designed to fit MX 11 and 13 liter engines

OEM	ENGINE	NON-OCF 38MT+	INTEGRATED OCF 38MT+	TEETH/PINION/PITCH	MELCO
PACCAR	MX 11/13	8200977	8201084	12 Tooth, Mod 3 Metric	D61-1003-001 D61-6002-011 M009T72578 M9T72578 PC2578 1847916



® For Customer Service or Technical Assistance call 800-372-0222

01 | 2024
DELCOREMY.COM